

# Enterprise Workstation Support Frame

# FE33M8406XX-00

Double-sided, Twin Tube Support Frame with 48" high Vertical Chase

**Services on Left Post**  
Pre-piped to top of post  
(see below for Piping Options)  
Indicate service(s) required

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Electric on Left Post**  
Pre-wired as selected below  
Indicate outlet device type

☐ 1 Device ☐ 2 Devices  
☐ 120VAC Duplex  
☐ 120VAC GFCI Duplex  
☐ \_\_\_\_\_

**Left – Data Option – Right**  
**Data Port on Service Chase**  
☐ Standard cutout - 1 1/4" x 2"  
☐ \_\_\_\_\_  
**Data Port Wiring**  
☐ no wiring  
☐ 3ft ☐ 4ft ☐ 5ft ☐ 6ft ☐ 8ft (atop)  
☐ Cat-6 ☐ \_\_\_\_\_  
☐ data port on both front & back

**Service Chase Receptacles**  
(back same as front)  
(see options below)

**Service Fittings**  
☐ W-0604-00 Ball Valve  
☐ W-0605-00 Needle Point  
☐ \_\_\_\_\_

**Services on Right Post**  
Pre-piped to top of post  
(see below for Piping Options)  
Indicate service(s) required

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Electric on Right Post**  
Pre-wired as selected below  
Indicate outlet device type

☐ 1 Device ☐ 2 Devices  
☐ 120VAC Duplex  
☐ 120VAC GFCI Duplex  
☐ \_\_\_\_\_

**Length:** (pick one only)  
☐ 42" ☐ 48"

<p><b>Power Options:</b> (indicate options required)  <b>Electrical Device Color</b> (pick one only)  <input type="checkbox"/> Black <input type="checkbox"/> Ivory <input type="checkbox"/> _____</p> <p><b>Service Chase Receptacles</b> (pick one only)  <input type="checkbox"/> Two (2) 120 VAC, 20 amp, Duplex (each side)  <input type="checkbox"/> Two (2) 120 VAC, 20 amp, GFCI, Duplex (each side)  <input type="checkbox"/> None  <input type="checkbox"/> _____</p> <p><b>Service Chase/Post Electric Wiring</b> (pick one only)  <input type="checkbox"/> 3ft <input type="checkbox"/> 4ft <input type="checkbox"/> 5ft <input type="checkbox"/> 6ft <input type="checkbox"/> 8ft (above top of post)  <input type="checkbox"/> Single Circuit pigtail, twist-lock plug  <input type="checkbox"/> Double Circuit pigtail, twist-lock plug  <input type="checkbox"/> None  <input type="checkbox"/> _____</p> <p><input type="checkbox"/> White Wire Color <input type="checkbox"/> Black Wire Color (pick one only)</p> <p><b>Specify Extension Hoses Separately</b></p>	<p><b>Electrical Pigtail Location</b> (pick one only)  <input type="checkbox"/> Top of Left Upright  <input type="checkbox"/> Top of Right Upright</p> <p><b>Piping Options:</b> (indicate options required)  <b>Piping Option</b> (pick one only)  <input type="checkbox"/> Pipe to top of post  <input type="checkbox"/> Pipe to top of post with extra:  <input type="checkbox"/> 3ft <input type="checkbox"/> 4ft <input type="checkbox"/> 5ft <input type="checkbox"/> 6ft <input type="checkbox"/> 8ft of hose  <input type="checkbox"/> _____</p> <p><b>Piping/Hose End Option</b> (pick one only)  <input type="checkbox"/> 3/8" IPS Threaded Female (standard)  <input type="checkbox"/> 3/8" IPS Threaded Male  <input type="checkbox"/> Keyed Male Quick-Connect W-8111-K_ <input type="checkbox"/> _____</p> <p><b>Support Frames are tested and certified to UL standard 61010-1 when pre-wired with cataloged fixtures.</b></p>
---	---

<b>FE33M8406</b> <input type="text"/> <input type="text"/> <b>-00</b>	COLOR	ITEM NO.	QUANTITY
PROJECT NAME:			